



2012-08-02

# Hierarchical Task Networks in COMBATXXI, Bringing AI Techniques Into Closed Form Combat Simulations

Reeves, David

Monterey, California: Naval Postgraduate School.



Calhoun is a project of the Dudley Knox Library at NPS, furthering the precepts and goals of open government and government transparency. All information contained herein has been approved for release by the NPS Public Affairs Officer.

**Dudley Knox Library / Naval Postgraduate School  
411 Dyer Road / 1 University Circle  
Monterey, California USA 93943**

<http://www.nps.edu/library>



# **Hierarchical Task Networks in COMBATXXI**

Bringing AI Techniques Into  
Closed Form Combat Simulations

David Reeves & Imre Balogh

# Agenda

- Introduction & Motivation
- Hierarchical Task Networks (HTN)
- HTNs in Dynamic Environments
- HTNs in COMBATXXI
- Future Work

# Introduction

- Goal of Research:
  - Develop better way to build complex behaviors in combat models
  - Target simulations are analytical combat simulations
    - Techniques apply to any simulation where autonomous agents are used
- Background:
  - Analytical Simulations
    - System/TTP evaluation
    - Tend to be closed form – no user interaction during runs
      - Highly Scripted
      - or **Autonomous Agents**
  - COMBATXXI
    - Analytical Sim used by the Army and Marines
    - Stochastic, entity level, event stepped, closed form model
  - Sponsored by Marine Corps Combat Development Command

# Hierarchical Task Networks

- HTNs are a type of automated planning system in which dependency between actions/tasks is expressed in the form of networks or trees
- The planning process starts with a high-level description of the problem as a set of goal tasks
- To accomplish the goal tasks, a plan is defined through action decomposition
- A set of sub-tasks is produced that must be sequenced appropriately to complete the higher-level task while accounting for constraints
- Sub-tasks may need further decomposition
- This process is repeated recursively until the sub-tasks are no longer decomposable.

# HTN Tasks

- Primitive Tasks – Tasks that require no further decomposition to be performed
- Compound Tasks – Tasks that need to be decomposed into a simpler set of tasks
- Goal Tasks – Tasks that, when completed, corresponds to the goal of the network or tree

A goal task corresponds to the achievement of the desired world state

- Constraint Node – condition to control network branch to be executed




# HTN Example: Go to Store

## START TREE (L to R)

- 'Go To Store' task starts plan generation
- 'Go To Store' (compound task) passes to the first node- 'have Keys'

## PASSES CONSTRAINT


- 'Get In Car' (primitive task) executes and passes to 'Drive To Store'.
- 'Drive To Store' (primitive task) executes and passes to 'Arrive At Store'.
- 'Arrive At Store' (goal task) completes the plan





# HTN Example: Go to Store

## Resulting Plan




**Plan execution system  
executes the plan**



# HTN Example: Go to Store

## START TREE (L to R)

- 'Go To Store' task starts plan generation
- 'Go To Store' (compound task) passes to the first node- 'have Keys'




## FAILS CONSTRAINT

- 'Walk To Store' (primitive task) executes and passes to 'Arrive At Store'
- 'Arrive At Store' (goal task) completes the plan

# HTN Example: Go to Store

## Resulting Plan



**Plan execution system  
executes the plan**

# HTNs in Dynamic Environments

- An HTN driven plan is based on values of the constraints at the time of plan formulation
  - Not a problem in static environments
- In a dynamic environment, there is no guarantee that the plan can be completed just because it was possible to generate it
- To account for changing environments, a method is needed to review the validity of the plan as it is being executed
- Generating plans can be expensive, so regeneration needs to be limited if possible

# “Replan” Events

- In event-stepped simulations, entities can be aware of the events that can affect their state
- By selectively listening to events that could affect their plans, entities can control how often they must regenerate their plans
- To take advantage of this we introduce a new type of event, the “replan event”, which will cause the entity to suspend the execution of the current plan and reevaluate the HTN being used
- In the process of defining an HTN, part of the specification is the set of events that can generate a replan event

# HTNs in COMBATXXI

- A COMBATXXI HTN tree is made up of nodes arranged in a network with constraints that determine which branches of the tree are processed as the plan is run
- There are three types of nodes in a COMBATXXI HTNs
  - Default Node: This is a basic node. No special actions are taken when the planner encounters a default node
  - Interrupt Node: An interrupt node tells the planner that it has reached a node for which it should no longer continue processing nodes. The plan is “interrupted” and stops, but is not finished
  - Goal Node: A goal node is a node that tells the planner that it’s reached a spot for which the world state is now in the desired state. The plan is finished and will be removed

# Interrupt Goal Task

- An interrupt goal represents a task that, when completed, will have the world state be closer to our final goal state, but is not the final goal state of the entire HTN
- Interrupt goal tasks serve two purposes:
  - Represent tasks that takes some time to complete and are likely places where the plan may be interrupted
  - Allow for the “lazy generation” of the plan – only part of plan needs to be generated
- Regeneration of plans are tied to specific events
- Interrupt goal are represented by red circles





# 'Go to Store' in COMBATXXI


• Replan event is "Stopped Moving"

## UNEXPECTED EVENT TRIGGERED

- If while driving, the car died and the entity was not at the store, the "Stopped Moving" event would still be published.
- HTN tree would execute and the entity would end up walking to the store.

## START TREE

- 'Go to Store' task starts execution
- 'At Store?' (constraint) is not true, pass to 'At Home?'
- 'At Home?' (constraint) is assumed true, pass to 'Have Keys?'
- 'Have Keys?' (constraint) is assumed true, pass to 'Get In Car'
- 'Get In Car' (default node) causes entity to get in car, pass to 'Drive To Store'
- 'Drive To Store' (interrupt node) executes and the planner will stop but the tree is not yet finished



## "STOP MOVING" EVENT TRIGGERED


- 'Go to Store' task starts execution
- 'At Store?' is true, pass to 'Arrive At Store'
- 'Arrive At Store' (goal node) indicates the world is at the desired state
- HTN is finished and the plan is removed.



# HTN Portability & Re-use

- To support building modular and reusable HTNs, parameters were added to the HTNs in COMBATXXI
  - Allows for creation of HTNs that can be used in multiple contexts
- With the introduction of interrupt nodes and HTN controlled replans, an HTN needs to be able to set and query status information accumulated as it executes
  - Status information can then be used in preconditions or tasks to affect the flow of the plan and execution of its tasks
  - To support this, all HTNs have their own “variable space” attached
  - Tasks are allowed to set and query variables in this variable space

# Graphical User Interface



- Full function Graphical HTN developed
  - Tailored for COMBATXXI
- Extensive helper functionality to help user build actions
- Supports saving parts of HTN to support reuse
- Based in interface metaphors used in common programming IDEs such as NetBeans and Eclipse

# Use in Recent Analysis

- This HTN methodology was recently rigorously tested in a complex scenario co-developed at NPS and the Marine Corps Combat Development Command
- This scenario was used to support analysis of the Amphibious Combat Vehicle (ACV)
- The scenario was composed of over 4000 entities executing complex maneuvers to include an amphibious landing, movement to contact, a bridge crossing, and a final attack supported by vehicles in a support by fire position
- HTNs were used to model each of these complex maneuvers and numerous others
- This approach allowed us to raise dynamic behaviors in COMBATXXI to a new level of sophistication

# Future Work

- Continue to refine this methodology based on experiences with using it to support the ACV AoA
- Develop ways that support building “reusable” HTNs that will help define libraries of HTN based behaviors
- Investigate extending HTNs to support a notion of “inheritance” that will allow for the definition of abstract HTNs
- Investigating machine learning (e.g. reinforcement learning) can be used with HTNs